

# **ISIFLO Flexi-Adapter**



Isiflo Sprint Flexi-Adapter is a repair coupling for use on all types of plastic and metal pipes except multi-layer pipes (e.g. Alu-Pex). This coupling ensures a tight and end-load resistant connection. For use in combination with Isiflo Brass couplings.

Visit www.isiflo.com for more details.

# 1. Product Description

Materials	PA12/GF, POM, acid proof steel (AISI 316) or Aluminum Bronze (35-50 mm and 49-63 mm) and EPDM O-ring with grease.
Dimension	20-27 mm, 27-35 mm, 35-50 mm and 49-63 mm
Max working pressure	16 bar
Temperature range	Up to +40°C
Medium	Water (16 bar), Air (10bar). Other medium; contact Isiflo for details.
Approvals	Sintef Certification PS1457
Surface treatment	None
Color	Black
Other information	Not for use on multi-layer pipes (e.g. Alu-Pex). Can be used in sea water. Can be buried.

mar. 21 Page 1 of 2



# 2. Description of use and Maintenance

## Cleaning

Can be cleaned with mild soap water. Use a clean and damped cloth.

# Inspection and control

Check for leakage.

## **Maintenance instruction and intervals**

No maintenance necessary.

# 3. Operation Technical Information

# Estimated technical lifetime without replacements:

>50 years.

# Warranty and conditions:

20 years against fabrication errors.

#### Moisture resistance:

Not affected by moisture.

# **Easiness of cleaning:**

Good.

#### Other information:

Composite: To be recycled as general waste at end of life.

POM: Plastic recycling.

Steel an Alu-bronze: Metal waste

O-rings: General waste

## Product details and instructions for use:

www.isiflo.com

### 4. Contact

Producer/manufacturer	Isiflo AS
Adress	Box 143
Postcode and city	2831 Raufoss, Norway
Phone	(+47) 61152700
E-mail	info@isiflo.com
Web	www.isiflo.com

mar. 21 Page 2 of 2