

ISIFLO BRASS THREADED FITTINGS



Isiflo Brass Threaded Fittings are threaded pipe fittings made in dezincification resistant brass used for joining in combination with hemp, thread tape or similar. Cylindrical threads on male and female parts in compliance with ISO 228/1.

For more information visit www.isiflo.com

1. Product Description

Materials	RA455 (CW625N) – Dezincification resistant brass
Dimension	1/8" – 4"
Max working pressure	16 bar
Temperature range	-20°C to +110°C
Medium	Water (16 bar), Air (10bar), Glycol and Ethanol. Other medium; contact Isiflo for details.
Approvals	Sintef Certification PS0041
Surface treatment	None
Color	Brass
Other information	Avoid connection to other metals as this can induce galvanic corrosion. Can be buried.

2. Description of use and Maintenance

Cleaning

Can be cleaned with mild soap water. Use a clean and damped cloth.

Inspection and control

Check for leakage.

Maintenance instruction and intervals

No maintenance necessary.

3. Operation Technical Information

Estimated technical lifetime without replacements: >50 years.
Warranty and conditions: 20 years against fabrication errors.
Moisture resistance: Not affected by moisture.
Easiness of cleaning: Good.
Other information: Brass: To be recycled as metal
Product details and instructions for use: www.isiflo.com

4. Contact

Producer/manufacturer	Isiflo AS
Adress	Box 143
Postcode and city	2831 Raufoss
Phone	(+47) 61152700
E-mail	info@isiflo.com
Web	www.isiflo.com