

## ISIFLO Composite GT-Fittings



Isiflo GT-Fittings are composite threaded pipe fittings for joining in combination with hemp, thread tape or similar. The fittings are produced in composite material according to EN 1254-4, cylindrical threads according to ISO 228-1.

Visit [www.isiflo.com](http://www.isiflo.com) for more details.

### 1. Product Description

<b>Materials</b>	PA12/GF
<b>Dimension</b>	3/4" – 2"
<b>Max working pressure</b>	16 bar
<b>Temperature range</b>	Up to +60°C
<b>Medium</b>	Water and tap water (16 bar), Air (10bar). Other medium; contact Isiflo for details.
<b>Approvals</b>	-
<b>Surface treatment</b>	None
<b>Color</b>	Black
<b>Other information</b>	Can be used for under ground installation. Can be used as a galvanic insulator.

## 2. Description of use and Maintenance

### Cleaning

Can be cleaned with mild soap water. Use a clean and dampened cloth.

### Inspection and control

Check for leakage.

### Maintenance instruction and intervals

No maintenance necessary.

## 3. Operation Technical Information

### Estimated technical lifetime without replacements:

>50 years.

### Warranty and conditions:

20 years against fabrication errors.

### Moisture resistance:

Not affected by moisture.

### Easiness of cleaning:

Good.

### Other information:

Composite: To be recycled as general waste at end of life.

### Product details and instructions for use:

[www.isiflo.com](http://www.isiflo.com)

## 4. Contact

<b>Producer/manufacturer</b>	Isiflo AS
<b>Address</b>	Box 143
<b>Postcode and city</b>	2831 Raufoss
<b>Phone</b>	(+47) 61152700
<b>E-mail</b>	<a href="mailto:info@isiflo.com">info@isiflo.com</a>
<b>Web</b>	<a href="http://www.isiflo.com">www.isiflo.com</a>