

## ISIFLO Sprint – PVC



Isiflo Sprint push fittings for PVC-pipes according to EN-1452 gives a tight and end-load resistant connection. The couplings are easy to use and gives a reliable long-term connection. Assembly without need for special tools.

Visit [www.isiflo.com](http://www.isiflo.com) for more details.

### 1. Product Description

<b>Materials</b>	PA12/GF, POM, stainless steel and EPDM O-rings
<b>Dimension</b>	20-63 mm
<b>Max working pressure</b>	16 bar
<b>Temperature range</b>	Up to +40°C
<b>Medium</b>	Water (16 bar), Air (10bar). Other medium; contact Isiflo for details.
<b>Approvals</b>	-
<b>Surface treatment</b>	None
<b>Color</b>	Black/Grey
<b>Pipes</b>	PVC according to EN-1452.
<b>Other information</b>	Can be buried.

## 2. Description of use and Maintenance

### Cleaning

Can be cleaned with mild soap water. Use a clean and dampened cloth.

### Inspection and control

Check for leakage.

### Maintenance instruction and intervals

No maintenance necessary.

## 3. Operation Technical Information

### Estimated technical lifetime without replacements:

>50 years.

### Warranty and conditions:

20 years against fabrication errors.

### Moisture resistance:

Not affected by moisture.

### Easiness of cleaning:

Good.

### Other information:

Composite: To be recycled as general waste at end of life.

POM and O-rings: General waste.

### Product details and instructions for use:

[www.isiflo.com](http://www.isiflo.com)

## 4. Contact

<b>Producer/manufacturer</b>	Isiflo AS
<b>Address</b>	Box 143
<b>Postcode and city</b>	2831 Raufoss
<b>Phone</b>	(+47) 61152700
<b>E-mail</b>	<a href="mailto:info@isiflo.com">info@isiflo.com</a>
<b>Web</b>	<a href="http://www.isiflo.com">www.isiflo.com</a>